
















Rare Earth Magnetic Bases - Multi-purpose

| Part No. | Image | Drawing | Pull Strength | Mounting | Case Material | Magnet Material | Max. Temp. |
|--|---|---|--|---|--------------------|-----------------|---|
| MH137-1A |  |  | 10 lbs. (5 kg) | 1/4-28 Integral Stud | Stainless Steel | Neodymium | 80°C |
| | | | Multi-Purpose Magnetic Base Low Profile for Small Sensors | | | |  |
| MH112-1A |  |  | 30 lbs. (14 kg) | 1/4-28 Integral Stud | Stainless Steel | Neodymium | 80°C |
| | | | Multi-Purpose Magnetic Base Low Profile | | | |  |
| MH128-1A |  |  | 30 lbs. (14 kg) | 1/4-28 Mounting Hole | Stainless Steel | Neodymium | 80°C |
| | | | Multi-Purpose Magnetic Base | | | |  |
| MH114-3A |  |  | 50 lbs. (23 kg) | 1/4-28 Mounting Hole | Stainless Steel | Neodymium | 80°C |
| | | | Multi-Purpose Magnetic Base Low Profile | | | |  |
| MH214-3A with Hexagonal Wrench |  |  | 50 lbs. (23 kg) | 1/4-28 Integral Rotating Mounting Nut | Stainless Steel | Neodymium | 80°C |
| | | | | | | |  |

Product Purpose

For Use With AC116-1A/AC216-1A Magnet Mount Accelerometer

The MH214-3A Easy Positioning Curved Surface Magnet can be adjusted so that the 2 poles of the magnet can be parallel to the data collector cable, perpendicular to the data collector cable, or in any rotational reference to the data collector cable that you like. An aluminum hex wrench is included with each magnet for easy adjustment.



magnet feet parallel with sensor cable



magnet feet perpendicular with sensor cable



magnet feet rotated with sensor cable

